

GypAcoustic Pro

Mineral Fibre Ceiling Board.



GypAcoustic Pro Mineral Fibre Ceiling Board is composed of 85% mineral wool, showcasing excellent fireproof properties, high humidity resistance, sound absorption capabilities, and effective heat insulation performance. With a diverse range of textures, GypAcoustic Pro Mineral Fibre Ceiling Board is well-suited for various decorative applications.

What's more, GypAcoustic Pro Mineral Fibre Ceiling Board is free from pollutants and hazardous substances such as formaldehyde or asbestos.

CHARACTERISTICS

Mineral fibre ceiling board comprising organic and composite fibres, with emulsion paint surface finish.


RECOMMENDED USE

Suitable for ceilings in lobbies, offices, conference rooms, corridors, department stores, auditoriums, hospitals, etc.

PRODUCT TEXTURE



PRODUCT FORMAT

Nominal Thickness	14mm
Nominal Weight	3.5kg/m ²
Nominal Density	260 - 280kg/m ³
Actual Metric Size	595mm x 595mm 595mm x 1195mm
Actual Imperial Size	603mm x 603mm 603mm x 1210mm
Edge Type	SQUARE 



GypAcoustic Pro offers a versatile array of textures, making it suitable for a wide range of decorative applications.

Gyproc® GypAcoustic Pro

NOISE REDUCTION COEFFICIENT

- NRC rating = 0.5

RELATIVE HUMIDITY

- Up to 90%

LIGHT REFLECTANCE VALUE

- $\leq 87\%$

HANDLING AND WORKABILITY

- Lightweight
- Quick and easy installation

INSTALLATION

- When installing GypAcoustic Pro Mineral Fibre Ceiling boards, ensure that the relative humidity in the application environment does not exceed the value specified for the product.
- Complete any wet projects before installing the boards.
- Design and install larger lamps or other heavy objects separately.
- Always wear clean gloves while working.
- After installation, be attentive to room ventilation, and remember to close doors and windows during rainy weather.

The images provided are for reference only. Kindly obtain confirmation from Gyproc's Technical Support Personnel before submission of specification for any project. The information in this literature is accurate at the time of publishing. The publisher reserves all rights to revise the product specifications without prior notice. It is the user's responsibility to ensure that the information communicated here is current before use and that the information provided here is for guidance only. Users must ensure that they are fully conversant with the products and systems before specification or installation. (GypAcoustic Pro, 2025)



SAINT-GOBAIN (SINGAPORE) PTE LTD
2 Venture Drive,
#13-18, Vision Exchange,
Singapore 608526.
☎ +65 6330 8288 📠 +65 6330 8289
🌐 www.saint-gobain.sg



SAINT-GOBAIN MALAYSIA SDN BHD
No 1 Jalan Sultan Mohamad 4.
Kawasan Perindustrian Bandar Sultan Suleiman.
42000 Port Klang, Selangor D E. Malaysia.
☎ +603 3169 5588 📠 +603 3169 5688
🌐 www.saint-gobain.my

