

# ShaftLiner

*A fire-resistant structure to protect elements in confined spaces wherever access is limited to one side only.*



ShaftWall provides a protective structure which can be incorporated at an early stage of construction without the need for scaffolding. It can be fully assembled from the room side of the shaft as it can be built from one side. The wall is specified as a high performance fire-rated wall between two elements where conventional construction from both sides would not be practical.

Gyproc ShaftWall system forms a wall of minimum 94mm thick, and it can accommodate vertical, deflection, and satisfy exacting height and pressure requirements. It provides up to 2 hours fire rating in accordance to BS 476: Part 20 & 22, and meets the highest severe duty rating in accordance with BS 5234: Part 2.


## CHARACTERISTICS

ShaftWall system comprises of GypFrame® CH-Stud and GypFrame® E-Stud, with channel section to perimeter and abutments. ShaftLiner is located between the studs and is secured using GypFrame® J-Runner. Provision is made for fire-stopping at the head and also over horizontal joints in the ShaftLiner. FireLine® forms the lining.

## RECOMMENDED USE

Commercial use in offices, shops, hotels, institutional, leisure, hospitals, and much more.

## PRODUCT FORMAT

Nominal Thickness	25mm
Nominal Weight	20.00kg/m <sup>2</sup>
Nominal Sheet Size	610mm x 2440mm
Edge Type	SQUARE EDGE 

## HANDLING AND WORKABILITY

- Lightweight
- Quick and easy installation

**Gyproc ShaftWall system forms a wall of minimum 94mm thick, and it can accommodate vertical, deflection, and satisfy exacting height and pressure requirements.**

#### FIRE RATING

- Non-combustible in accordance to BS 476: Part 4
- Low fire propagation in accordance to BS 476: Part 6
- Class 1 surface spread of flame in accordance to BS 476: Part 7
- Classified as Class 0 material in accordance to BS 476: Part 6 & 7
- Low flame spread index <25 in accordance to ASTM E84
- Providing up to 2 hours fire rating in accordance to BS 476: Part 20 & 22

#### MANUFACTURING SPECIFICATIONS

- In compliance with BS EN 520

#### QUALITY ASSURANCE

- Product is manufactured in a facility certified to ISO 14001, ISO 45001, ISO 9001

#### HEALTH AND ENVIRONMENTAL CONTRIBUTIONS

- Made from 100% natural gypsum
- Recyclable material, environmentally friendly
- Green-labelled product endorsed by the Singapore Green Building Council
- Does not produce toxic fumes or hazardous substances that are harmful to health

The images provided are for reference only. Kindly obtain confirmation from Gyproc's Technical Support Personnel before submission of specification for any project. The information in this literature is accurate at the time of publishing. The publisher reserves all rights to revise the product specifications without prior notice. It is the user's responsibility to ensure that the information communicated here is current before use and that the information provided here is for guidance only. Users must ensure that they are fully conversant with the products and systems before specification or installation. (ShaftLiner.2024)



**SAINT-GOBAIN (SINGAPORE) PTE LTD**  
2 Venture Drive,  
#13-18, Vision Exchange,  
Singapore 608526.

+65 6330 8288 +65 6330 8289

[www.saint-gobain.sg](http://www.saint-gobain.sg)



**SAINT-GOBAIN MALAYSIA SDN BHD**  
No 1 Jalan Sultan Mohamad 4,  
Kawasan Perindustrian Bandar Sultan Suleiman,  
42000 Port Klang, Selangor D E. Malaysia.

+603 3169 5588 +603 3169 5688

[www.saint-gobain.my](http://www.saint-gobain.my)

