


## Weberfloor Sports Court Base/Primer

Acrylic, water-based paint, uniform non-slip finish


Weberfloor Sports Court Base/Primer is an acrylic, water-based paint ideal for all types of sports courts. Due to its specially graded mineral fillers, it offers a uniform and non-slip finish. Weberfloor Sports Court Base/Primer is available with non-slip aggregate to facilitate application by squeegee.



### PRODUCT BENEFITS



**WATER  
BASED**



**EXCELLENT  
ADHESION**



**SLIP  
RESISTANT**

### USES

Weberfloor Sports Court Base/Primer provides a non-slip finish for tennis, volleyball, netball, and multi-purpose courts. It is recommended as a decorative and protective coating for bituminous and concrete surfaces but is not suitable for areas where groundwater is likely to rise through the substrate.

### ADVANTAGES

- Non-reflective and non-skid
- No fire hazards
- Eco-friendly, low VOC, odourless
- Excellent adhesion to concrete, or any bitumen
- Excellent UV resistance
- Fast dry

### TECHNICAL DATA & PHYSICAL PROPERTIES

<b>Base</b>	
<b>Colour</b>	Black
<b>Flammability</b>	Non-Flammable
<b>Curing Time (Ventilated Area)</b>	8 - 14 hours
<b>Thickness</b>	2 - 3 mm
<b>Primer (Add 20% of clean water)</b>	
<b>Colour</b>	Black
<b>Weigh Solids</b>	64 ± 2 %
<b>Flammability</b>	Non-Flammable
<b>Curing Time (Ventilated Area)</b>	6 - 12 hours

Specifications are subject to change without notification. Results shown are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance will depend on installation methods and site conditions.

### PRECAUTION

Optimal results are achieved when Weberfloor Sports Court Base/Primer is applied in the morning or evening under lights. Weberfloor Sports Court Base/Primer should not be applied when the temperature is below 10°C, the concrete's temperature is over 35°C, or if there is an imminent threat of rain.

### CONSUMPTION

Weberfloor Sports Court Primer - Approx. 0.3 kg/m<sup>2</sup> @ 0.1 mm  
Weberfloor Sports Court Base - Approx 1.4 kg/m<sup>2</sup> @ 1 mm

#### SAINT-GOBAIN (SINGAPORE) PTE LTD

2 Venture Drive, #13-18,  
Vision Exchange, Singapore 608526

(65) 63308288 (65) 63308289

eis.info@saint-gobain.com www.saint-gobain.sg

#### SAINT-GOBAIN WEBER (M) SDN BHD

No 29 & 31, Jalan TIAJ 2/1, Taman Industri Alam Jaya,  
42300 Bandar Puncak Alam, Selangor D E, Malaysia

(603) 60389498/97/89 (603) 6038 9507

info.webermalaysia@saint-gobain.com www.mys.weber

## Weberfloor Sports Court Base/Primer

Acrylic, water-based paint, uniform non-slip finish

### PROCEDURE & APPLICATION



#### Surface Preparation

All surfaces must be clean, sound, and free from any laitance, oil, grease, and any contaminants. Remove any residual paint with paint stripper, scraping, grinding and sand blasting.

New concrete surfaces must be porous and cured for  $\geq 28$  days. It must be etched, using a high pressure water blaster ( $\geq 3000$  psi) with a solution of hydrochloric acid and water of 1:10. The acid solution is to be evenly distributed with a stiff broom. Allow it to sit on the surface for  $\geq 15$  minutes before cleaning with a water blaster. Fill saw cuts and movement joints with cement grout.

New asphalt surfaces should be cured for  $\geq 18$  days. Use high pressure water blaster. Avoid unnecessary filling by laying a tight and even top course of asphalt. Open, aged or deteriorated asphalt should be repaired.



#### Mixing & Application

Mix Part A and Part B thoroughly. Pour a “wind row” of Weberfloor Sports Court Base/Primer onto the court and apply quickly and evenly with a flexible rubber squeegee. Touch dry is 1-1.5 hours at  $25^{\circ}\text{C}$ . Apply the next coat after  $\geq 4$  hours depending on temperature. The system would require 1-2 coats of Weberfloor Sports Court Primer and a minimum of 2 coats of Weberfloor Sports Court Base.

The area can withstand light use after 24-48 hours, however, full cure could take up to 7 days depending on drying conditions.

### CLEANING

Clean the tools and equipment immediately after use with clean water.

### STORAGE & PACKING

Weberfloor Sports Court Primer/Base is available in 39 kg set. (Part A - 18 kg pail + Part B - 21 kg pail).

Shelf life of Weberfloor Sports Court Primer and Weberfloor Sports Court Base is 9 months and 12 months, respectively, if unopened and kept in temperature of  $5^{\circ}\text{C}$  to  $30^{\circ}\text{C}$ .

### HEALTH & SAFETY

There should be good ventilation. If not, a portable exhaust fan shall be used. Wear protective clothing, gloves, and goggles during mixing and application process. Handle with care and in the event of eyes and skin contact, wash with plenty of water, and seek medical attention if irritation persists. Please keep out of reach of children.

\*Note: Because it is not possible to give specific instructions for the various site conditions or to control the applications, the information on this Technical Data Sheet is for general guidance only. Saint-Gobain (Singapore) Pte Ltd reserves the rights to amend the contents of the data sheet at its sole discretion. (Jan '23)



#### SAINT-GOBAIN (SINGAPORE) PTE LTD

2 Venture Drive, #13-18,  
Vision Exchange, Singapore 608526

(65) 63308288 (65) 63308289

eis.info@saint-gobain.com www.saint-gobain.sg

#### SAINT-GOBAIN WEBER (M) SDN BHD

No 29 & 31, Jalan TIAJ 2/1, Taman Industri Alam Jaya,  
42300 Bandar Puncak Alam, Selangor D E, Malaysia

(603) 60389498/97/89 (603) 6038 9507

info.webermalaysia@saint-gobain.com www.mys.weber