

Trade name **E.Mix Easi Plaster Eco**

1 IDENTIFICATION OF HAZARDOUS CHEMICAL AND OF THE SUPPLIER

Product identifier

Trade name **E.Mix Easi Plaster Eco**

Safety data sheet no.: XXP017750

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Plaster

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain (Singapore) Pte Ltd
2 Venture Drive, #13-18, Vision Exchange, Singapore 608526
Phone: +65 6330 8288
Fax.: +65 6330 8288

2 HAZARDS IDENTIFICATION

Classification of the substance or mixture



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation

Label elements GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS05 GHS07

Signal word **Danger**

Hazard-determining components of labelling:

cement portland, chemicals

Printing date 07.12.2023

Version Number 3

Revision: 07.12.2023

Trade name E.Mix Easi Plaster Eco

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national /International regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances

3 COMPOSITION AND INFORMATION OF THE INGREDIENTS

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:		
CAS: 471-34-1 EINECS: 207-439-9	calcium carbonate	>50%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, chemicals Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limits: Skin Irrit. 2; H315: C $\geq$ 1 % Eye Dam. 1; H318: C $\geq$ 1 %	10-25%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16

4 FIRST AID MEASURES

Description of first aid measures

General information

Immediately remove any clothing soiled by the product. Never administer anything by mouth to an unconscious person. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Seek medical treatment in case of complaints

In case of unconsciousness place patient stably inside position for transportation.

Trade name E.Mix Easi Plaster Eco
--

After skin contact

Immediately wash with water and soap and rinse thoroughly. Immediately rinse with water.
If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

Information for doctor

Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents The product is not combustible. Use fire extinguishing methods suitable to surrounding conditions.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: Wear fully protective suit.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear protective clothing.
Avoid contact with skin and eyes.
Avoid formation of dust.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Pick up mechanically.
Dispose of the material collected according to regulations.
Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 HANDLING AND STORAGE

Handling

Precautions for safe handling

Prevent formation of dust.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace. Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required. The product is not flammable

Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles. Store in a cool location.

Information about storage in one common storage facility: Store away from food stuffs. Store away from water

Further information about storage conditions: Store in cool, dry conditions in well-sealed receptacles. Protect from humidity and water.

Specific end use(s) No further relevant information available.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see section 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 471-34-1 calcium carbonate		
Inhalative	Derived No Effect Level	6.36 mg/m ³ (worker local long term value) 1.06 mg/m ³ (consumer local long term value)
PNECs		
CAS: 65996-69-2 Slags, ferrous metal, blast furnace		
Predicted No-Effect Concentration		1,000 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration		500 mg/l (sea water rating factor)
Predicted No-Effect Concentration		5,000 mg/l (fresh water rating factor)
CAS No. Designation of material % Type Value Unit		
CAS: 471-34-1 calcium carbonate		

Printing date 07.12.2023

Version Number 3

Revision: 07.12.2023

Trade name E.Mix Easi Plaster Eco	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)TLV	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
(USA)	TLV withdrawn
CAS: 65997-15-1 cement portland, grey	
PEL (USA)	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction
REL(USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
CAS: 65997-18-1 Cement, Portland, chemicals	
PEL (Malaysia)	Long-term value: 10mg/m ²
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn

Additional Occupational Exposure Limit Values for possible hazards during processing:

Total inhalable dust: 10 mg/m³

Respirable dust: (< 5 µm): 4 mg/m³

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid close or long term contact with the skin

Respiratory protection:

Short term filter device: Filter P2

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: Protective gloves.

Material of gloves Nitrile rubber, NBR

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	Powder
Colour:	According to product specification
Odour:	Uncharacteristic
Odour threshold:	Not determined.
pH-value:	Alkaline in water
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
Flash point:	Not applicable
Flammability (solid, gas):	Product is not flammable.
Ignition temperature:	Product is not self-igniting.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined..
Explosive properties:	Not determined
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Oxidising properties	Not determined.
Vapour pressure:	Not applicable.
Density at 20 °C:	1.5 g/cm ³ (DIN 51757)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Miscible
Segregation coefficient (n-octanol/water) log	
Pow:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent content:	
EU-VOC (%)	0.0000 %
EU-VOC (g/L)	0.00000 g/l
Solids content:	100.0 %
Other information	None.

Printing date 07.12.2023

Version Number 3

Revision: 07.12.2023

Trade name **E.Mix Easi Plaster Eco**

10 STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions

Reacts with acids

Conditions to avoid Avoid water ingress/moisture during storage (the product will react with moisture and harden)

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 TOXICOLOGICAL INFORMATION

Information on toxicological effects **Acute toxicity**

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 471-34-1 calcium carbonate			
Oral	LD50	6,450 mg/kg (Rat)	
Dermal	LD50	6,450 mg/kg (Rat)	
CAS: 65997-15-1 cement portland, chemicals			
Dermal	LD50	>2,000 mg/kg (Rabbit)	
CAS: 65996-69-2 Slags, ferrous metal, blast furnace			
Oral	LD50	>2,000 mg/kg (Rat)	
Dermal	LD50	>4,000 mg/kg (Rat)	

Primary irritant effect:

Skin corrosion/irritation: Irritant to skin and mucous membranes.

Serious eye damage/irritation: Strong irritant with the danger of severe eye injury.

Respiratory or skin sensitization: Sensitisation possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: Irritant

12 ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: Not further relevant information available

Type of test	Effective concentration	Method	Assessment
CAS: 471-34-1 calcium carbonate			
EC50/72h	14 mg/l	(Algae)	

Printing date 07.12.2023

Version Number 3

Revision: 07.12.2023

Trade name E.Mix Easi Plaster Eco

CAS: 65996-69-2 Slags, ferrous metal, blast furnace

LC50/96h	>100 mg/l (Leuciscus idus (Orfe))
LC0/96h	>100 mg/l (Leuciscus idus (Orfe))
EC50/72h	>90,000 mg/l (Algae)
NOEC (72h)	50-100 mg/l (Algae)
NOEC (21d)	1,563 mg/l (Daphnia magna)
EC 0/48h	>100 mg/l (Daphnia magna)

Persistence and degradability No further relevant information available.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Behavioral in sewage processing plants

Type of test/ Effective concentration/ Method/ Assessment

CAS: 65996-69-2 Slags, ferrous metal, blast furnace

EC 50 (3h)	>10,000 mg/l (Activated sludge)
------------	---------------------------------

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

Other adverse effects No further relevant information available.

13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish.

Possible waste code 17 09 04

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Thoroughly shake out sacks.

14 TRANSPORT INFORMATION

UN-Number

ADR, ADN, IMDG, IATA

Void

UN proper shipping name

ADR, ADN, IMDG, IATA

Void

Printing date 07.12.2023

Version Number 3

Revision: 07.12.2023

Trade name E.Mix Easi Plaster Eco	
Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
Packing group ADR, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications
ADR Remarks:	Not classified as a dangerous goods for transport
IMDG Remarks:	Not classified as a dangerous goods for transport
IATA Remarks:	Not classified as a dangerous goods for transport
UN "Model Regulation":	Void

15 REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixtureGHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

cement portland, chemicals

Hazard statements

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause allergic skin reaction.
H335	May cause respiratory irritation.

Precautionary statements

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.

Printing date 07.12.2023

Version Number 3

Revision: 07.12.2023

Trade name E.Mix Easi Plaster Eco
--

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: R&D Department

Contact:

Abdul Hadi Bin MOHAMAD SHOKRI

AbdulHadi.MOHAMADSHOKRI@saint-gobain.com

Abbreviations and acronyms:

RID: Reglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations)

Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3