

1 IDENTIFICATION OF HAZARDOUS CHEMICAL AND OF THE SUPPLIER

Product identifier

Trade name **E.Mix Joint Mortar**

Safety data sheet no.: XXP017024

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Ready-to-use mortar

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain (Singapore) Pte Ltd
2 Venture Drive, #13-18, Vision Exchange, Singapore 608526
Phone: +65 6330 8288
Fax.: +65 6330 8288

2 HAZARDS IDENTIFICATION

Classification of the substance or mixture



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

Label elements GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause allergic skin reaction.
H335 May cause respiratory irritation.

Trade name E.Mix Joint Mortar

Precautionary statements

P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children.
P103	Read label before use.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

3 COMPOSITION AND INFORMATION OF THE INGREDIENTS

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOTSE 3, H335	25-50%
CAS: 471-34-1 EINECS: 207-439-9	calcium carbonate	10-25%

SVHC Void

Additional information

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8). For the wording of the listed hazard phrases refer to section 16.

4 FIRST AID MEASURES

Description of first aid measures

General information

Immediately remove any clothing soiled by the product. Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly. Immediately rinse with water.

Printing date 29.11.2023

Version Number 3

Revision: 29.11.2023

Trade name E.Mix Joint Mortar

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting.
Seek medical attention and present this data sheet.

Information for doctor

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

5 FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents The product is not combustible.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid formation of dust. Ensure adequate ventilation.

Environmental precautions: No special measures required.

Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 HANDLING AND STORAGE

Handling

Precautions for safe handling

Thorough dedusting.

Keep receptacles tightly sealed.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities

Printing date 29.11.2023

Version Number 3

Revision: 29.11.2023

Trade name E.Mix Joint Mortar

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles. Protect from humidity and water.

Specific end use(s) No further relevant information available.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs	
CAS: 471-34-1 calcium carbonate	
Inhalative	Derived No Effect Level 6.36 mg/m ³ (worker local long term value) 1.06 mg/m ³ (consumer local long term value)
CAS No.	Designation of material % Type Value Unit
CAS: 65997-15-1 cement portland, grey	
PEL (Malaysia)	Long-term value: 10 mg/m ³
PEL (USA)REL	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction
(USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 1* mg/m ³ E; *as respirable fraction
CAS: 471-34-1 calcium carbonate	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)TLV	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
(USA)	TLV withdrawn

Additional Occupational Exposure Limit Values for possible hazards during processing:

Total inhalable dust: 10 mg/m³ Respirable dust (< 5 µm): 4 mg/m³

Quartz respirable dust (< 5 µm) : 0,15 mg/m³

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Printing date 29.11.2023

Version Number 3

Revision: 29.11.2023

Trade name E.Mix Joint Mortar

Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
Use a moisturising skin cream after processing the product.

Respiratory protection:

Not necessary if room is well-ventilated.
Short term filter device:
Filter P2.
In case of brief exposure or low pollution use respiratory filter device.
In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: Protective gloves.

Material of gloves Nitrile impregnated cotton gloves complying with the standard EN 374-1.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	Powder
Colour:	Grey
Odour:	Uncharacteristic.
Odour threshold:	Not determined.
pH-value:	Alkaline
Change in condition	
Melting point/freezing point:	Undeter
Initial boiling point and boiling range:	mined. 2,230 °C (DIN)
Flash point:	Not applicable
Flammability (solid, gas):	Product is not flammable.
Ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not applicable
Upper:	Not applicable
Oxidising properties	Not determined.
Vapour pressure at 1732 °C:	13.5 hPa (DIN 51640)Not applicable.
Density at 20 °C:	1.6 g/cm3 (DIN 51757)

Printing date 29.11.2023

Version Number 3

Revision: 29.11.2023

Trade name E.Mix Joint Mortar	
Relative density	Not applicable.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with Water:	Hardens when in contact with water.
Segregation coefficient (n-octanol/water) log Pow:	Not determined.
Viscosity:	
dynamic:	Not applicable.
kinematic:	Not applicable.
Solvent content:	
EU-VOC (%)	0.00 %
EU-VOC (g/L)	0.0 g/l
Solids content:	100.0 %
Other information	None.

10 STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions Reacts with acids

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 65997-15-1 cement portland, grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)
CAS: 471-34-1 calcium carbonate			
Oral	LD50	6,450 mg/kg	(Rat)
Dermal	LD50	6,450 mg/kg	(Rat)

Primary irritant effect:

Skin corrosion/irritation Irritant to skin and mucous membranes.

Serious eye damage/irritation Strong irritant with the danger of severe eye injury.

Respiratory or skin sensitisation Sensitisation possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Printing date 29.11.2023

Version Number 3

Revision: 29.11.2023

Trade name E.Mix Joint Mortar

Irritant

12 ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test Effective concentration Method Assessment	
CAS: 471-34-1 calcium carbonate	
EC50/72h 14	mg/l (Algae)

Persistence and degradability

No further relevant information available.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: The product contains substances which causes severe clouding in water

Remark: The product causes a significant pH change. Neutralise before introduction.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

Other adverse effects No further relevant information available.

13 DISPOSAL CONSIDERATIONS

Waste treatment methods Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish.

Possible waste code 17 09 04.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Thoroughly shake out sacks.

14 TRANSPORT INFORMATION

UN-Number	
ADR, ADN, IMDG, IATA	Void
UN proper shipping name	
ADR, ADN, IMDG, IATA	Void

Page 7 of 10

Printing date 29.11.2023

Version Number 3

Revision: 29.11.2023

Trade name E.Mix Joint Mortar	
Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
Packing group ADR, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
ADR	
Remarks:	Not classified as a dangerous goods for transport
IMDG	
Remarks:	Not classified as a dangerous goods for transport
IATA	
Remarks:	Not classified as a dangerous goods for transport
UN "Model Regulation":	Void

15 REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Trade name E.Mix Joint Mortar

H317 May cause allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand
P102 Keep out of reach of children.
P103 Read label before use.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out

16 OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: R&D Department

Contact:

Teh Kim Heok
Phone: +603-60389094/9084
KimHeok.Teh@saint-gobain.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern (REACH regulation)
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/ irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Trade name E.Mix Joint Mortar

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.