

## SAFETY DATA SHEET

### WEBERDRY ES 119 (ROOT RESISTANT WATERPROOFING MEMBRANE)

Printing date 01.06.2025

Version number 1

Revision: 01.06.2025

#### 1 IDENTIFICATION OF HAZARDOUS CHEMICAL AND OF THE SUPPLIER

Product Name: WEBERDRY ES 119  
Root Resistant Waterproofing Membrane  
Company Name: Saint-Gobain (Singapore) Pte Ltd  
Address: 2 Venture Drive #13-18 Vision Exchange Singapore 608526  
Telephone: 6363 5340  
Fax: 6363 5988  
Email: eis.info@saint-gobain.com

#### 2 HAZARDS IDENTIFICATION

**Flammability:** Non-flammable

**Classification:** Non-Dangerous Goods (Bitumen Emulsion)

No component is present at sufficient concentration to require a hazardous classification.

No major hazard exists. It is, however, advised that the product is used in well-ventilated areas, and prolonged exposure to the fumes avoided. Repeated or prolonged skin exposure should be avoided.

**Safety:** Wear suitable protective clothing and gloves. May cause irritation by skin contact. Good working practices, high standards of personal hygiene and premises cleanliness must be maintained at all times.

#### 3 COMPOSITION OF THE INGREDIENTS

Asphalt	15% - 90%	CAS no. 8052-42-4
Mineral Fillers	> 5%	CAS no. 014807-96-6
Copolymers, if any	> 0%	CAS not required
Water	> 5%	CAS no. 7732-18-5
Additives and Surfactants, if any		

#### 4 FIRST AID MEASURES

**Skin Contact:** Occasional contact is unlikely to have an adverse effect except on particularly sensitive skin. As a general precaution, avoid repeated or prolonged contact. Wear proper attire such as gloves to minimise contact. Hot product may cause burn though this product does not require heating to use. Wash skin immediately with plenty of water and soap. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation occurs. Use a proprietary hand cleaner if the product has dried. Seek medical assistance if irritation persists.

**Eye Contact:** Unlikely to cause damage when product is cold. However, avoid any eye contact if possible. Wear proper protective gear such as eye shields. Will cause burn if product is hot; seek medical help. Immediately flush eyes with plenty of clean water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists.

**Oral Ingestion:** While consumption of this in large quantities should not occur, unless intentional, do not induce vomiting. Wash out mouth with water. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to

## SAFETY DATA SHEET

### WEBERDRY ES 119 (ROOT RESISTANT WATERPROOFING MEMBRANE)

Printing date 01.06.2025

Version number 1

Revision: 01.06.2025

drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Wash hands thoroughly prior to food consumption. Avoid eating in application site.

**Inhalation:** Always use in well ventilated areas and use suitable respirators, if necessary. Remove to fresh air immediately if headache, nausea or dizziness occurs. Keep person warm and at rest. If not breathing or if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Seek medical assistance if symptoms persist. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

**Notes to Physician:** Basic aid, decontamination, symptomatic treatment.

#### 5 FIRE-FIGHTING MEASURES

**Extinguishing media:** In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.

Fire in confined spaces should be dealt with by trained personnel wearing approved breathing apparatus. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Special exposure hazards:** In a fire or if heated, a pressure increase will occur and the container may burst. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

#### 6 ACCIDENTAL RELEASE MEASURES

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

**Environmental Precautions:** Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Large Spill:** Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local

## SAFETY DATA SHEET

### WEBERDRY ES 119 (ROOT RESISTANT WATERPROOFING MEMBRANE)

Printing date 01.06.2025

Version number 1

Revision: 01.06.2025

regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

**Small Spill:** Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Causes slippery surfaces when wet. If spillage has occurred in a confined space, ensure adequate ventilation.

#### 7 HANDLING AND STORAGE

**Handling:** Used only in a well-ventilated area. Wash thoroughly after handling. Avoid prolonged or repeated breathing of vapour. Avoid prolonged or repeated contact with skin.

Put on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

**Storage:** Store in well-ventilated area. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION/ENGINEERING CONTROLS

**Exposure limit values:** Not available.

Always use with adequate ventilation.

**Respiratory Protection:** Always use in well ventilated areas and use suitable respirators, if necessary. Remove to fresh air immediately if headache, nausea, or dizziness occurs. Keep person warm and at rest. If not breathing or if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Seek medical assistance if symptoms persist.

**Skin Protection:** For brief contact, no precautions other than clean body-covering clothing should be need. Always use impervious gloves such as neoprene. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations <1 hours (breakthrough time): Polychloroprene - CR or PVC gloves.

## SAFETY DATA SHEET

### WEBERDRY ES 119 (ROOT RESISTANT WATERPROOFING MEMBRANE)

Printing date 01.06.2025

Version number 1

Revision: 01.06.2025

**Eye Protection:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Recommended: safety glasses with side-shields.

**Hygiene Measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dark/Greyish Brown. Paste  
Solubility: Water soluble

#### 10 STABILITY AND REACTIVITY

Material is stable and unlikely to react in a hazardous manner under normal conditions of use.

Conditions to avoid: Hazardous decomposition products: Carbon monoxide, Carbon dioxide, hydrogen chloride. In a fire, decomposition may produce toxic gases/fumes.

No hazardous reactions when used as directed.

#### 11 TOXICOLOGICAL INFORMATION

Will cause burn if material is hot. When material is heated at to high temperatures, vapour, mists or fumes will be given off and may condense, contaminating the skin or irritating the eyes.

At normal ambient temperatures, this material will be unlikely to present an inhalation hazard.

#### 12 ECOLOGICAL INFORMATION

This material is not biodegradable.

#### 13 DISPOSAL CONSIDERATIONS

Examine possibilities for re-utilisation. Product residues and uncleaned empty containers should be packaged, sealed, labelled, and disposed of or recycled according to relevant national and local regulation. Where large quantities are concerned, consult the supplier.

#### 14 TRANSPORT INFORMATION

Not classified as hazardous for Transport.  
Poisons Schedule: Not scheduled.

## SAFETY DATA SHEET

### WEBERDRY ES 119 (ROOT RESISTANT WATERPROOFING MEMBRANE)

Printing date 01.06.2025

Version number 1

Revision: 01.06.2025

#### 15 REGULATORY INFORMATION

Poisons Schedule: Not Scheduled

#### 16 OTHER INFORMATION

SRC SSR2401

BDF QG

Note: Whilst every effort is made to ensure that the contents of this material is accurate and current, it is the user's responsibility to satisfy itself of the suitability of products for its own particular purpose. As the actual use by others is beyond our control, EMIX does not provide any guarantee, implied or expressed, as to the effects of such use. No liability is accepted by EMIX and/or its staff, for any loss or damage, direct or indirect, that may result from using the product, information or adopting recommendations and/or suggestions as actual conditions for use are beyond our control. This information is not to be construed as absolutely complete since additional information may be necessary or desirable for exceptional or particular circumstances.