

Trade name Weberfloor PUC SL (Part A)

1 IDENTIFICATION OF HAZARDOUS CHEMICAL AND OF THE SUPPLIER

Product identifier

Trade name: Weberfloor PUC SL (Part A)

Substance: Polyurethane Self-Smoothing Screed

CAS No: Mixture

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain (Singapore) Pte Ltd

2 Venture Drive, #13-18 Vision Exchange, Singapore 608526

Phone: +65 6330 8288

Fax: +65 6330 8288

Saint-Gobain Weber (M) Sdn Bhd

No 29 & 31, Jalan TIAJ 2/1, Taman Industri Alam Jaya,

42300 Bandar Puncak Alam, Selangor D E, Malaysia

Phone: +603 6038 9498/97/89

Fax: +603 6038 9507

2 HAZARDS IDENTIFICATION

Classification

Repr. 1B

Aquatic Acute 1B

Hazard Pictograms



Signal Word

Danger

Hazard Statements

H400 Very toxic to aquatic life

H360 May damage fertility or to unborn child

Precautionary Statements

P201 Obtain special instruction before use

P202 Do not handle until all safety precautions have been read and understood

P273 Avoid release to the environment

P281 Use personal protective equipment as required

P308+P313 IF exposed or concerned: Get medical advice/attention

P391 Collect spillage

P405 Store locked up

P501 Dispose of contents/container in accordance with applicable regulations

3 COMPOSITION AND INFORMATION OF THE INGREDIENTS

Chemical Name	CAS Number	%
DIBUTYL 1, 2-BENZENEDICARBOXYLATE <i>Repr. 1B H360</i> <i>Aquatic Acute 1 H400</i>	84-74-2	≥3 %

Trade name Weberfloor PUC SL (Part A)

4 FIRST AID MEASURES

Description of first aid measures

After inhalation:

Move affected person to fresh air. If breathing has stopped, perform artificial respiration. Seek medical advice if symptoms persist.

After skin contact:

Wash skin thoroughly with soap and water. Remove contaminated clothing. If symptoms persist, seek medical advice.

After eye contact:

Rinse eyes immediately with plenty of clean water for at least 15 minutes and seek medical advice if irritation persists.

After swallowing:

Do not induce vomiting. Dilute with water. Seek medical attention immediately.

5 FIRE-FIGHTING MEASURES

Extinguishing media

In case of fire, use water spray (fog) foam, CO₂ or dry chemical.

Fire Fighting Instruction

Fire fighters should wear self-contained breathing apparatus and full protective gear.

Self Ignition

Not self igniting.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Environmental precautions

Limit leakages with earth or sand. Do not discharge into the subsoil/soil.

Methods and materials for containment and cleaning up

Take up with absorbing materials (e.g sand, universal binder). Dispose as hazardous waste.

7 HANDLING AND STORAGE

Handling

Ensure adequate ventilation at the workplace. Avoid open flames and sources of ignition.

Storage

Keep away from food and drink. Store in a cool dry area and keep container tightly sealed.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering controls: Use with adequate general and local exhaust ventilation.

Hygiene Measures: Remove contaminated clothing immediately after work. Launder clothing that is soiled with this material before reuse, or else discard. Inform individuals responsible for the cleaning of potential hazards associated with the handling of these contaminated clothing. No smoking, eating, or drinking at the workplace. Wash hands thoroughly after handling this material. Keep workplace clean.

Respiratory Protection: General room ventilation is required.

Hand Protection: Chemical resistance gloves/ PVC gloves.

Eye/Face Protection: Safety goggles with side shields.

Skin Protection: Light protective clothing.

Trade name Weberfloor PUC SL (Part A)

9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Odour:	Typical
Colour:	White Emulsion
Chemical Type:	Liquid
Flammability:	Does not ignite
Boiling Point:	No data available
Melting Point:	No data available
Explosion Hazard:	Not explosive
Vapour Pressure (25°C):	N/A
Solubility:	Insoluble in water
Relative Density:	1,047 g/cm ³ @ 20°C

10 STABILITY AND REACTIVITY

Chemical stability: Stable under normal temperature and pressure.

Polymerization: Will not polymerize.

Thermal decomposition products: Oxides of carbon.

11 TOXICOLOGICAL INFORMATION

Toxicity Data:

- LD50: >20ml/kg Skin – rabbit, 7499mg/kg Oral – rat.
- LC50: 4250mg/m³ Inhalation – rat.

Local effects: Irritant (Inhalation, eye).

Acute toxicity level: Toxic (Inhalation), Slightly toxic (Ingestion).

Medical conditions: Kidney problem

Aggravated exposure

Mutagenic data: Available

Reproductive effects data: Available

12 ECOLOGICAL INFORMATION

Eco toxicity data:

Fish toxicity:	700 µg/l 96hours LC50 (Mortality) – Bluegill
Invertebrate toxicity:	5400 µg/l 7hours EC50 (Regeneration) – Flatworm
Algal toxicity:	3.4 µg/l 96year EC50 (Growth) – Dinoflagellate
Other toxic:	340 µg/l 2weeks (Population) – Aquatic community

Fate and transport:

Bio concentration: 3500 µg/l 24day BCF (Residue) – Midge 0.18 µg/l

13 DISPOSAL CONSIDERATIONS

Product: In accordance with local regulations, take to special waste incineration plant.

Contaminated Packaging: If empty contaminated containers are recycled or disposed of, the receiver must inform about possible hazards.

Trade name Weberfloor PUC SL (Part A)

14 TRANSPORT INFORMATION

UN NUMBER: UN3082
(Rail/Road) ADR/RID Shipping Data
Proper Shipping Name: Environmentally Hazardous Substances, Liquid, N.O.S
Hazard Class: 9
Packing Group: III
(Sea) IMO Shipping Data
Proper Shipping Name: Environmentally Hazardous Substances, Liquid, N.O.S
Hazard Class: 9
Packing Group: III
(Air) ICAO/IATA Shipping Data
Proper Shipping Name: Environmentally Hazardous Substances, Liquid, N.O.S
Hazard Class: 9
Packing Group: III

15 REGULATORY INFORMATION

Applicable regulations:

- 1 – Permissible workplaces exposure standard labour
- 2 – Labelling of hazardous chemicals
- 3 – Liberal rule, traffic regulations
- 4 – Method and facility Standard for Industrial Waste Storage, Clearance and Disposal

16 OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Trade name Weberfloor PUC SL (Part B)

1 IDENTIFICATION OF HAZARDOUS CHEMICAL AND OF THE SUPPLIER

Product identifier

Trade name: Weberfloor PUC SL (Part B)

Substance: Polyurethane heavy duty screed floor coating

CAS No: Substance

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain (Singapore) Pte Ltd

2 Venture Drive, #13-18 Vision Exchange, Singapore 608526

Phone: +65 6330 8288

Fax: +65 6330 8288

Saint-Gobain Weber (M) Sdn Bhd

No 29 & 31, Jalan TIAJ 2/1, Taman Industri Alam Jaya,

42300 Bandar Puncak Alam, Selangor D E, Malaysia

Phone: +603 6038 9498/97/89

Fax: +603 6038 9507

2 HAZARDS IDENTIFICATION

Classification

Acute toxicity, Inhalative, Category 4 (H332), Skin irritation, Category 2 (H315), Eye irritation, Category 2 (H319),

Sensitization of the respiratory airways, Category 1 (H334), Sensitization of the skin, Category 1 (H317), Carcinogenicity, Category 2 (H351), Specific target organ toxicity (single exposure), Category 3 (H335) Specific

target organ toxicity (repeated exposure), Category 2 (H373)

Hazard Pictograms



Signal Word

Danger

Hazard Statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause allergic skin reaction.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/eye protection/face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Move affected person to fresh air and keep at rest in a position comfortable for breathing.

Trade name Weberfloor PUC SL (Part B)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/attention.

3 COMPOSITION AND INFORMATION OF THE INGREDIENTS

Chemical Name	CAS Number	%
Diphenylmethane-diisocyanate, isomers and homologues <i>Acute Tox. 4 Inhalative H332 Skin Irrit. 2 H315 Eye Irrit. 2 H319 Resp. Sens. 1 H334 Skin Sens. 1 H317 Carc. 2 H351 STOT SE 3 H335 STOT RE 2 Inhalative H373</i> <i>Specific threshold concentration:</i> <i>Eye Irrit. 2 H319 >= 5 %</i> <i>Skin Irrit. 2 H315 >= 5 %</i> <i>Resp. Sens. 1 H334 >= 0,1 %</i> <i>STOT SE 3 H335 >= 5 %</i>	9016-87-9	<=98%

4 FIRST AID MEASURES

Description of first aid measures

General advice

Soiled, soaked clothing and shoes must be immediately removed, decontaminated and disposed of.

After inhalation

Move affected person to fresh air and keep him/her warm, let him/her rest. If there is difficulty in breathing, medical advice is required.

After skin contact

Wash the contacted area thoroughly with water and a polyethylene glycol based cleanser. Consult a doctor in the event of a skin reaction.

After eye contact

Wash eyes immediately with plenty of clean water for at least 10 minutes and seek medical advice if irritation persists.

After swallowing

Do not induce vomiting. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Notes to physician: The product irritates the respiratory tract and may trigger sensitisation of the skin and respiratory tract. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Extended medical treatment may be required depending on the degree of exposure and the severity of the symptoms.

Indication of any immediate medical attention and special treatment needed

Therapeutic measures: No information available.

5 FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Carbon dioxide (CO₂), Foam, extinguishing powder, in cases of larger fires, water spray should be used.

Unsuitable extinguishing media: High volume water jet.

Special hazards arising from the substance or mixture: Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen, isocyanate vapors and traces of hydrogen cyanide. In the event of fire and/or explosion do not breathe fumes. Fire in vicinity poses risk of pressure build-up and rupture. Containers at risk from fire should be cooled with water and, if possible, removed from the danger area.

Advice for firefighters

During fire-fighting respirator with independent air-supply and airtight garment is required. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

Trade name Weberfloor PUC SL (Part B)

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Put on protective equipment (see section 8). Ensure adequate ventilation/exhaust extraction. Keep unauthorized persons away.

Environment related measures

Do not allow to escape into waterways, wastewater or soil.

Methods and material for containment and cleaning up

Remove mechanically; cover the remainder with wet, absorbent material (e.g. sawdust, chemical binder based on calcium silicate hydrate, sand). After approx. one hour transfer to waste container and do not seal (evolution of CO₂). Keep damp in a safe ventilated area for several days. Spill area can be decontaminated with the following recommended decontamination solution: Decontamination solution 1: 8-10% sodium carbonate and 2% of liquid soap in water Decontamination solution 2: Liquid/yellow soap (potassium soap with ~15% anionic tenside): 20ml; Water:700ml; Polyethyleneglycol (PEG 400): 350ml

Reference to other sections: For further disposal measures see section 13.

7 HANDLING AND STORAGE

Handling

Provide sufficient air exchange and/or exhaust in work rooms.

In all workplaces or parts of the plant where high concentrations of isocyanate aerosols and/or vapours may be generated (e.g. during pressure release, mould venting or when cleaning mixing heads with an air blast), appropriately located exhaust ventilation must be provided in order to prevent occupational exposure limits from being exceeded. The air should be drawn away from the personnel handling the product. The efficiency of the exhaust equipment should be periodically checked. The threshold limit values noted in section 8 must be monitored.

The personal protective measures described in section 8 must be observed. Contact with skin and eyes and inhalation of vapours must be avoided under all circumstances.

Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at end of work and use skin-protecting ointment. Keep working clothes separately. Take off all contaminated clothing immediately.

Decontaminate, destroy and dispose of soiled protective clothing (see Section 13).

Storage

Keep container tightly closed and dry. Further information on the storage conditions which must be observed to preserve quality can be found in our product information sheet.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Use with adequate general and local exhaust ventilation.

Hygiene Measures: Do not eat, drink, smoke or drug taking in workplace. Wash hands before break or after work.

Respiratory Protection: General room ventilation is required.

Hand Protection: Chemical resistance gloves/ PVC gloves.

Eye/Face Protection: Safety goggles with side shields.

Skin Protection: Light protective clothing.

9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

General Information

Appearance:	Liquid
Colour:	Brown
Odour:	Earthy, musty
Odour Threshold:	Not established
pH:	Not applicable
Pour Point:	< 0°C (ISO 3016)
Boiling Point/Range:	> 300°C at 1.013 hPa (DIN 53171)
Flash Point:	> 200°C
Evaporation Rate:	Not established
Flammability (solid, gas):	Not applicable
Burning Number:	Not applicable
Vapour Pressure:	Diphenyl-methane-diisocyanate, (MDI) < 0,00001 hPa at 20°C < 0,0005 hPa (50°C) For products with a very low vapour pressure, the apparent vapour pressure may exceed the vapour pressure of the pure product due to conditions of manufacturing, storage or transportation, e.g. by solved gases like nitrogen or carbon dioxide. 1 hPa at 20°C EG A4 12 hPa at 50°C EG A4 17 hPa at 55°C EG A4
Vapour Density:	Not established
Density:	1,238 g/cm ³ at 20°C (DIN 51757)
Miscibility with water:	Immiscible at 15°C
Surface tension:	Not established
Partition coefficient: (n-octanol/water)	Not established
Auto-ignition Temperature:	Not applicable
Ignition Temperature:	> 500°C (DIN 51794)
Decomposition Temperature:	Not established
Viscosity, dynamic:	>= 200 mPa.s at 20°C (DIN 53019)
Explosive properties:	Not established
Dust explosion class:	Not applicable
Oxidising properties:	Not established

Other information

The indicated values do not necessarily correspond to the product specification. Please refer to the technical information sheet for specification data.

10 STABILITY AND REACTIVITY

Reactivity: This information is not available.

Chemical stability: Polymerises at about 200°C with evolution of CO₂.

Possibility of hazardous reactions: Exothermic reaction with amines and alcohols; reacts with water forming CO₂; in closed containers, risk of bursting owing to increase of pressure.

Conditions to avoid: This information is not available.

Incompatible materials: This information is not available.

Hazardous decomposition products: No hazardous decomposition products when stored and handled correctly.

11 TOXICOLOGICAL INFORMATION

Please find below the data available to us:

Information on toxicological effects

Acute toxicity, oral

diphenylmethane-diisocyanate, isomers and homologues

LD50 rat, male/female: > 10,000 mg/kg

Method: OECD Test Guideline 401

Acute toxicity, dermal

diphenylmethane-diisocyanate, isomers and homologues

LD50 rabbit, male/female: > 9,400 mg/kg

Method: OECD Test Guideline 402

Acute toxicity, inhalation

diphenylmethane-diisocyanate, isomers and homologues

LC50 rat, male/female: 0.31 mg/l, 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

The test atmosphere generated in the animal study is not representative of workplace environments, how the substance is placed on the market, and how it can reasonably be expected to be used. Therefore, the test result cannot be directly applied for the purpose of assessing hazard. Based on expert judgment and the weight of the evidence, a modified classification for acute inhalation toxicity is justified.

Assessment: Harmful by inhalation.

Converted acute toxicity point estimate 1.5 mg/l

Test atmosphere: dust/mist

Method: Expert judgement

Primary skin irritation

diphenylmethane-diisocyanate, isomers and homologues

Species: rabbit Result: slight irritant

Method: OECD Test Guideline 404

Primary mucosae irritation

diphenylmethane-diisocyanate, isomers and homologues

Species: rabbit

Result: non-irritant

Method: OECD Test Guideline 405

Toxicological studies of a comparable product.

Sensitisation

diphenylmethane-diisocyanate, isomers and homologues

Skin sensitisation according to Magnusson/Kligmann (maximizing test)

Species: Guinea pig

Result: negative

Classification: Does not cause skin sensitization.

Method: OECD Test Guideline 406

Skin sensitization (local lymph node assay (LLNA))

Species: Mouse

Result: positive

Classification: May cause sensitization by skin contact.

Method: OECD Test Guideline 429

Toxicological studies of a comparable product.

Trade name Weberfloor PUC SL (Part B)

Respiratory sensitization

Species: rat

Result: positive

Classification: May cause sensitization by inhalation.

Subacute, subchronic and prolonged toxicity

diphenylmethane-diisocyanate, isomers and homologues

NOAEL: 0,2 mg/m³

LOAEL (Lowest observable adverse effect level): 1 mg/m³ application

Route: Inhalative

Species: rat, male/female

Dose Levels: 0 - 0,2 - 1 - 6 mg/m³

Exposure duration: 2 a

Frequency of treatment: 6 hours a day, 5 days a week

Target Organs: Lungs, Nasal inner lining

Test substance: as aerosol

Method: OECD Test Guideline 453

Findings: Irritation to nasal cavity and to lungs.

Studies of a comparable product.

Carcinogenicity

diphenylmethane-diisocyanate, isomers and homologues

Species: rat, male/female

Application Route: Inhalative

Dose Levels: 0 - 0,2 - 1 - 6 mg/m³

Test substance: as aerosol

Exposure duration: 2 a

Frequency of treatment: 6 hours/day, 5 days/week

Method: OECD Test Guideline 453

Occurrence of tumours in the highest dose group.

Reproductive toxicity/Fertility

diphenylmethane-diisocyanate, isomers and homologues

No data available.

Reproductive toxicity/Teratogenicity

diphenylmethane-diisocyanate, isomers and homologues

NOAEL (teratogenicity): 12 mg/m³

NOAEL (maternal): 4 mg/m³

NOAEL (developmental toxicity): 4 mg/m³

Species: rat, female

Application Route: Inhalative

Dose Levels: 0 - 1 - 4 - 12 mg/m³

Frequency of treatment: 6 hours/day (Exposure duration: 10 days (day 6 - 15 p.c.))

Test period: 20 d

Test substance: as aerosol

Method: OECD Test Guideline 414

NOAEL (developmental toxicity): 4 mg/m³

Did not show teratogenic effects in animal experiments.

Genotoxicity in vitro

diphenylmethane-diisocyanate, isomers and homologues

Test type: Salmonella/microsome test (Ames test)

Test system: Salmonella typhimurium

Metabolic activation: with/without

Trade name Weberfloor PUC SL (Part B)

Result: negative
Method: OECD Test Guideline 471

Genotoxicity in vivo
diphenylmethane-diisocyanate, isomers and homologues
Test type: Micronucleus test
Species: rat, male
Application Route: Inhalative (exposure period: 3x1h/day over 3 weeks)
Result: negative
Method: OECD Test Guideline 474
Studies of a comparable product.

STOT evaluation – one-time exposure
diphenylmethane-diisocyanate, isomers and homologues
Route of exposure: Inhalative
Target Organs: Respiratory Tract May cause respiratory irritation.

STOT evaluation – repeated exposure
diphenylmethane-diisocyanate, isomers and homologues
Route of exposure: Inhalative
Target Organs: Respiratory Tract
May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity
diphenylmethane-diisocyanate, isomers and homologues
Based on available data, the classification criteria are not met.

CMR Assessment
diphenylmethane-diisocyanate, isomers and homologues
Carcinogenicity: Suspected of causing cancer by inhalation (Carc. 2).
Mutagenicity: In vitro and in vivo tests did not show mutagenic effects. Based on available data, the classification criteria are not met.
Teratogenicity: Did not show teratogenic effects in animal experiments. Based on available data, the classification criteria are not met.
Reproductive toxicity/Fertility: Based on available data, the classification criteria are not met.

Toxicology Assessment
diphenylmethane-diisocyanate, isomers and homologues
Acute effects: Harmful if inhaled. The product causes irritation of eyes, skin and mucous membranes.
Sensitization: May cause sensitization by inhalation and skin contact.

Additional information
diphenylmethane-diisocyanate, isomers and homologues
Special properties/effects: Over-exposure entails the risk of concentration-dependent irritating effects on eyes, nose throat, and respiratory tract. Delayed appearance of the complaints and development of hypersensitivity (difficult breathing, coughing, asthma) are possible. Hypersensitive persons may suffer from these effects even at low isocyanate concentrations, including concentrations below the UK Workplace Exposure Limit (WEL).
Prolonged contact with the skin may cause tanning and irritant effects.

12 ECOLOGICAL INFORMATION

Do not allow to escape into waterways, wastewater or soil.

Toxicity

Acute Fish toxicity

diphenylmethane-diisocyanate, isomers and homologues

LC50 > 1,000 mg/l

Test type: Acute Fish Toxicity

Species: Danio rerio (zebra fish)

Exposure duration: 96 h

Method: OECD Test Guideline 203

Acute toxicity for daphnia

diphenylmethane-diisocyanate, isomers and homologues

EC50 > 1,000 mg/l

Test type: static test

Species: Daphnia magna (Water flea)

Exposure duration: 24 h

Method: OECD Test Guideline 202

Chronic toxicity to daphnia

diphenylmethane-diisocyanate, isomers and homologues

NOEC (Reproduction) > 10 mg/l

Species: Daphnia magna (Water flea)

Exposure duration: 21 d

Method: OECD Test Guideline 202

Acute toxicity for algae

diphenylmethane-diisocyanate, isomers and homologues

ErC50 > 1,640 mg/l

Test type: Growth inhibition

Species: scenedesmus subspicatus

Exposure duration: 72 h

Method: OECD Test Guideline 201

Acute bacterial toxicity

diphenylmethane-diisocyanate, isomers and homologues

EC50 > 100 mg/l

Test type: Respiration inhibition

Species: activated sludge

Exposure duration: 3 h

Method: OECD Test Guideline 209

Toxicity to soil dwelling organisms

diphenylmethane-diisocyanate, isomers and homologues

NOEC (mortality) > 1,000 mg/kg

Species: Eisenia fetida (earthworms)

Exposure duration: 14 d

Method: OECD Test Guideline 207

Toxicity to terrestrial plants

diphenylmethane-diisocyanate, isomers and homologues

NOEC (seedling emergence) > 1,000 mg/kg

Species: Avena sativa (oats)

Exposure duration: 14 d

Method: OECD Test Guideline 208

Trade name Weberfloor PUC SL (Part B)

NOEC (Growth rate) > 1,000 mg/kg
Species: Avena sativa (oats)
Exposure duration: 14 d
Method: OECD Test Guideline 208

NOEC (seedling emergence) > 1,000 mg/kg
Species: Lactuca sativa (lettuce)
Exposure duration: 14 d
Method: OECD Test Guideline 208

NOEC (Growth rate) > 1,000 mg/kg
Species: Lactuca sativa (lettuce)
Exposure duration: 14 d
Method: OECD Test Guideline 208

Ecotoxicology Assessment

diphenylmethane-diisocyanate, isomers and homologues

Acute aquatic toxicity: Based on available data, the classification criteria are not met.

Chronic aquatic toxicity: There is no evidence of a chronic aquatic toxicity.

Toxicity Data on Soil: Not expected to adsorb on soil. The substance is graded as non-critical to soil-dwelling organisms.

Impact on Sewage Treatment: Because of the low bacterial toxicity, there is no risk of an adverse effect on the performance of biological waste water treatment plants.

Persistence and degradability

Biodegradability

diphenylmethane-diisocyanate, isomers and homologues

Test type: aerobic

Inoculum: activated sludge

Biodegradation: 0 %, 28 d, i.e. not inherently degradable

Method: OECD Test Guideline 302 C

According to the results of tests of biodegradability this product is not readily biodegradable.

Stability in water

diphenylmethane-diisocyanate, isomers and homologues

Test type: Hydrolysis

Half-life: 20 h at 25°C

The substance hydrolyzes rapidly in water. Studies of a comparable product.

Photodegradation

diphenylmethane-diisocyanate, isomers and homologues

Test type: Phototransformation in air

Temperature: 25°C

sensitizer: OH-radicals

Concentration sensibilisator: 500,000 1/cm³

Half-life indirect photolysis: 0.92 d

Method: SRC - AOP (calculation)

After evaporation or exposure to the air, the product will be moderately degraded by photochemical processes. Studies of a comparable product.

Bioaccumulative potential

Bioaccumulation

diphenylmethane-diisocyanate, isomers and homologues

Bioconcentration factor (BCF): < 14

Species: Cyprinus carpio (Carp)

Trade name Weberfloor PUC SL (Part B)

Exposure duration: 42 d
Concentration: 0.2 mg/l
Method: OECD Test Guideline 305 C
An accumulation in aquatic organisms is not to be expected.
The substance hydrolyses rapidly in water.
Studies of hydrolysis products.

Mobility in soil

No data available.

Environmental distribution

diphenylmethane-diisocyanate, isomers and homologues
no data available

Results of PBT and vPvB assessment

No data available.

Other adverse effects

Isocyanate reacts with water at the interface forming CO₂ and a solid insoluble product with high melting point (polyurea). This reaction is accelerated by surfactants (e.g., detergents) or by water-soluble solvents. Previous experience shows that polyurea is inert and non-degradable.

13 DISPOSAL CONSIDERATIONS

Dispose in accordance with applicable international, national and local laws, ordinances and statutes. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

Waste treatment methods

After final product withdrawal, all residues must be removed from containers (drip-free, powder-free or paste-free). Once the product residues adhering to the walls of the containers have been rendered harmless, the product and hazard labels must be invalidated. These containers can be returned for recycling to the appropriate centres set up within the framework of the existing take-back scheme of the chemical industry. Containers must be recycled in compliance with national legislation and environmental regulations.

None disposal into waste water.

14 TRANSPORT INFORMATION

UN NUMBER:	Not dangerous for transport
(Rail/Road) ADR/RID Shipping Data:	Not regulated (Not dangerous for transport)
(Sea)IMO Shipping Data:	Not regulated (Not dangerous for transport)
(Air)ICAO/IATA Shipping Data:	Not regulated (Not dangerous for transport)
PACKING GROUP:	Not dangerous for transport

15 REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations Only China: Compliant with the following local regulations:
Only China: Decree 591 Regulations on the control over safety of hazardous chemicals
Only China: GB/T 16483 Safety data sheet for Chemical Products-Content and order of section
Only China: GB 13690 General rule for classification and hazard communication of chemicals GB 30000.2-29 Safety rules for classification and labelling of chemicals
Any existing national regulations on the handling of isocyanates must be observed.

16 OTHER INFORMATION

Full text of hazardous (H) warnings referred to under sections 2, 3 and 10 of the CLP classification (1272/2008/CE).

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

For internal US delivery: Under § 172.101, Appendix A, DOT (Department of Transportation) it is requested: MDI Reportable Quantity (RQ):5000lbs (2270kg).

ISOPA Guidelines for safe loading/unloading, transport and storage of TDI and MDI. ISOPA Order No.: PSC-0005- GUIDL

Safety precautions for handling freshly molded polyurethane parts:

Depending on the production parameters, any uncovered surfaces of freshly molded polyurethane parts using this raw material may contain traces of substances (e. g. starting and reaction products, catalysts, release agents) with hazardous characteristics. Skin contact with traces of these substances must be avoided. Therefore, during demolding or other handling of fresh molded parts, protective gloves tested according to DIN-EN 374 (e.g. nitrile rubber ≥ 1.3 mm thick, breakthrough time ≥ 480 min, or according to recommendations from glove maker's thinner gloves that need to be changed in compliance with breakthrough times more frequently) must be used. Depending on formulation and processing conditions, the requirements may be different from handling of the pure substances. Closed protective clothing is required for the protection of other areas of skin.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Trade name Weberfloor PUC SL (Part C)

1 IDENTIFICATION OF HAZARDOUS CHEMICAL AND OF THE SUPPLIER

Product identifier

Trade name: Weberfloor PUC SL (Part C)

Substance: Plain filler polyurethane screed

CAS No: Mixture

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain (Singapore) Pte Ltd

2 Venture Drive, #13-18 Vision Exchange, Singapore 608526

Phone: +65 6330 8288

Fax: +65 6330 8288

Saint-Gobain Weber (M) Sdn Bhd

No 29 & 31, Jalan TIAJ 2/1, Taman Industri Alam Jaya,

42300 Bandar Puncak Alam, Selangor D E, Malaysia

Phone: +603 6038 9498/97/89

Fax: +603 6038 9507

2 HAZARDS IDENTIFICATION

Classification

Skin Irrit. 2: May causes skin irritation.

Eye Dam. 1: Causes serious eye damage.

Skin Sens. 1B: May cause an allergic skin reaction.

STOT SE. 3: May cause respiratory irritation.

Hazard Pictograms



Signal Word

Danger

Hazard Statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Precautionary Statements

P260 Do not breathe dust.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P305+351+338 If In EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P501 Dispose of contents/container in accordance with local regulations Contains: Calcium oxide. When mixed with water it will form calcium hydroxide which has a corrosive effect on skin and eyes.

Trade name Weberfloor PUC SL (Part C)

3 COMPOSITION AND INFORMATION OF THE INGREDIENTS

Chemical Name	CAS Number	%
WHITE CEMENT Eye Dam. 1 H318 Skin Sens. 1B H317 Skin Irrit. 2 H315 Stot se 3 H335	65997-15-1	<80%
Silicon Dioxide	601-214-2	<10%

4 FIRST AID MEASURES

Description of first aid measures

After inhalation:

Move affected person to fresh air. If breathing has stopped, institute artificial respiration. Seek medical advice if symptoms persist.

After skin contact

Wash skin thoroughly with soap and water. Remove contaminated clothing. If symptoms persist, seek medical advice.

After eye contact

Rinse eyes thoroughly with water for at least 15 minutes, and seek medical advice.

After swallowing

Do not induce vomiting. Dilute with water. Seek medical examination immediately.

5 FIRE-FIGHTING MEASURES

Extinguishing Media: In case of fire, use water spray (fog) foam, dry chemical, or CO²

Fire Fighting Instruction: Fire fighters should wear self-contained breathing apparatus and full protective gear.

Self-ignition: Not self-igniting

Flash Point: No data available

6 ACCIDENTAL RELEASE MEASURES

Personal Precaution: Use personal protective equipment.

Environmental Precaution: Do not allow to enter drains or waterways, do not discharge into the subsoil/soil.

Methods for Cleaning Up: Take up with absorbent materials (e.g.: sand, universal binder). Dispose of as hazardous waste.

7 HANDLING AND STORAGE

Handling

Ensure adequate ventilation at the workplace. Avoid open flames and sources of ignition.

Storage

Keep away from food and drink. Store in a cool dry area and keep container tightly sealed.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Use with adequate general and local exhaust ventilation.

Hygiene Measure: Do not eat, drink, smoke or take drugs in the workplace. Wash hands before break or after work.

Respiratory Protection: General room ventilation is adequate.

Hand Protection: Chemical resistance gloves / PVC gloves.

Eye/Face Protection: Safety goggles with side shields.

Skin Protection: Light protective clothing.

Trade name Weberfloor PUC SL (Part C)

9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Odour:	Odourless
Chemical Type:	Mixture Powder
Flammability:	Does not ignite
Boiling Point:	No data available
Melting Point:	>1,000 °C
Explosion Hazard:	No data available
Vapour Pressure (25°C):	No data available
Solubility (25°C):	Insoluble in water
Relative Density:	No data available

10 STABILITY AND REACTIVITY

Stability: No specific test data related to reactivity available for this product or its ingredients.

Hazardous Polymerization: Will not occur. Avoid strong acid, strong base and amines.

Hazardous reactions: In fire, toxic fumes may be generated.

11 TOXICOLOGICAL INFORMATION

Proper use provided, no adverse health effects have been observed or have been come to our knowledge. Eye contact may produce an oil film over the eyeball causing a harmless reversible short-lasting dimness of sight.

12 ECOLOGICAL INFORMATION

Bioaccumulation: Not available

Fish Toxicity: Not available

13 DISPOSAL CONSIDERATIONS

Product: In accordance with local authority regulations, take to special waste incineration plant.

Contaminated packaging: If empty contaminated containers are recycled or disposed of, the receiver must inform about possible hazards.

14 TRANSPORT INFORMATION

UN Number: (Not Classified as hazardous)

(Rail/Road) ADR/RID Shipping Data: Not regulated (Not dangerous for transport)

(Sea) IMO Shipping Data: Not regulated (Not dangerous for transport)

(Air) ICAO/IATA Shipping Data: Not regulated (Not dangerous for transport)

Packing Group: -

15 REGULATORY INFORMATION

Applicable regulations:

1. Permissible workplaces exposure standard labour
2. Labelling of hazardous chemicals
3. Liberal rule, traffic regulation
4. Method and facility standard for industrial waste storage, clearance and disposal.

Trade name Weberfloor PUC SL (Part C)

16 OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Trade name Weberfloor PUC SL (Part D)

1 IDENTIFICATION OF HAZARDOUS CHEMICAL AND OF THE SUPPLIER

Product identifier

Trade name: Weberfloor PUC SL (Part D) Colour Paste

Substance: Colour Paste

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain (Singapore) Pte Ltd

2 Venture Drive, #13-18 Vision Exchange, Singapore 608526

Phone: +65 6330 8288

Fax: +65 6330 8288

Saint-Gobain Weber (M) Sdn Bhd

No 29 & 31, Jalan TIAJ 2/1, Taman Industri Alam Jaya,

42300 Bandar Puncak Alam, Selangor D E, Malaysia

Phone: +603 6038 9498/97/89

Fax: +603 6038 9507

2 HAZARDS IDENTIFICATION

Classification

Skin Irrit. 2: May causes skin irritation.

Skin Sens. 1: May cause sensitization by skin contact.

Hazard Pictograms



Signal Word

Warning

Hazard Statements

H316 Causes mild skin irritation

H317 May cause allergic skin reaction

Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/eye protection/face protection.

P333+P317 If skin irritation or rash occurs: Get medical help.

3 COMPOSITION AND INFORMATION OF THE INGREDIENTS

Chemical Name	CAS Number	%
Water	7732-18-5	≤ 25 %
Colour Pigment	68609-97-2	≥ 70 %

Trade name Weberfloor PUC SL (Part D)

4 FIRST AID MEASURES

Description of first aid measures

After inhalation:

Move affected person to fresh air. If breathing has stopped, institute artificial respiration. Seek medical advice if symptoms persist.

After skin contact:

Wash the contacted area thoroughly with soap and water. Remove contaminated clothing. If symptoms persist, seek medical advice.

After eye contact:

Rinse eyes immediately with plenty of clean water for at least 15 minutes and seek medical advice.

After swallowing:

Do not induce vomiting. Dilute with water. Seek medical examination immediately.

5 FIRE-FIGHTING MEASURES

Extinguishing media

In case of fire, use water spray (fog) foam, dry chemical or CO₂.

Fire Fighting Instruction

Fire fighters should wear self-contained breathing apparatus and full protective gear.

Self Ignition

Not self igniting.

Flash Point

> 250 °C.

6 ACCIDENTAL RELEASE MEASURES

Personal Precaution

Use personal protective equipment.

Environmental Precaution

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil.

Methods for Cleaning Up

Take up with absorbing materials (e.g. sand, universal binder). Dispose as hazardous waste.

7 HANDLING AND STORAGE

Handling

Ensure adequate ventilation at the workplace. Avoid open flames and sources of ignition.

Storage

Keep away from food and drink. Store in a cool dry area and keep container tightly sealed.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering controls: Use with adequate general and local exhaust ventilation.

Hygiene Measure: Do not eat, drink, smoke or take drugs in the workplace. Wash hands before break or after work.

Respiratory Protection: General room ventilation is adequate.

Protection of hands: Chemical resistance gloves/PVC gloves.

Eye protection: Safety goggles with side shields.

Skin protection: Light protective clothing.

Trade name Weberfloor PUC SL (Part D)

9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Odour:	Characteristic mild
Chemical Type:	Liquid
Flammability:	Does not ignite
Boiling Point:	No data available
Melting Point:	No data available
Explosion Hazard:	Not explosive
Vapour Pressure (25°C):	Not applicable
Solubility (250°C):	Insoluble in water
Relative Density:	1.16g/m ³

10 STABILITY AND REACTIVITY

Stability: Stable. Avoid static electricity discharge.

Hazardous Polymerization: Will not occur. Avoid strong acid, strong base and amines.

Hazardous Reactions: In fire, toxic fumes may be generated.

11 TOXICOLOGICAL INFORMATION

Proper use provided, no adverse health effects have been observed or have been come to our knowledge. Eye contact may produce an oil film over the eyeball causing a harmless reversible short lasting dimness of sight.

12 ECOLOGICAL INFORMATION

Bioaccumulation: Not available

Fish Toxicity: Not available

13 DISPOSAL CONSIDERATIONS

Product: In accordance with local authority regulations, take to special waste incineration plant.

Contaminated packaging: If empty contaminated containers are recycled or disposed of, the receiver must inform about possible hazards.

14 TRANSPORT INFORMATION

UN Number:	- (Not classified as hazardous)
(Rail/Road) ARD/RID Shipping Data:	Not regulated (Not dangerous for transport)
(Sea) IMO Shipping Data:	Not regulated (Not dangerous for transport)
(Air) ICAO/IATA Shipping Data:	Not regulated (Not dangerous for transport)
Packing Group:	-

15 REGULATORY INFORMATION

Hazard Labels:	Irritant
R43:	May cause sensation by skin contact
R36/38:	Irritating to eyes and skin
S24:	Avoid contact with skin
S26:	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S28:	In case of contact with skin, wash immediately with plenty of water and soap

Trade name Weberfloor PUC SL (Part D)

16 OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Technical Department

Contact: Tan Kim Song

Phone: +65 6363 5340

kimsong.tan@saint-gobain.com