

Weberfloor Road Marking

Modified acrylic chlorinated rubber road marking




Weberfloor Road Marking is a modified chlorinated rubber road marking paint. It is widely used for road traffic signs, road dividers, and other applications. It is most suitable for coating masonry surfaces, pavement bricks, premixed concrete, cement rendering, and concrete surfaces.

PRODUCT BENEFITS



ABRASION RESISTANT



EXCELLENT ADHESION



EASY TO APPLY

USES

Weberfloor Road Marking is for traffic signs on normal roads, pavement bricks, cement, etc. It is an excellent water-repellent paint with good adhesion, coverage, and hiding power.

ADVANTAGES

- Fast and easy application
- Improved water and alkaline resistance
- Excellent adhesion
- Excellent abrasion resistance

TECHNICAL DATA & PHYSICAL PROPERTIES

| | |
|----------------------------|------------------------------|
| Finish | Matt |
| Density @ 28°C | ± 1.4 g/ml |
| Viscosity @ 28°C | 7000 cps |
| Adhesive Strength | > 1.5 MPa (concrete failure) |
| Recommended D.F.T per coat | 200µ |
| Recoating time | Within 8 - 32 hours |

PROCEDURE & APPLICATION



Surface Preparation

All surfaces must be dry, clean, sound, and free from any laitance, oil, grease, and any contaminants.



Mixing

Mix using a suitable electrical stirrer (with 750 watt high power mixer) to mix for 2 minutes until fully homogenous.



Application

Apply emulsion polymer sealer. Do not apply if substrate temperature is <math>< 5^{\circ}\text{C}</math> above the dew point. Apply using a roller or a brush in 1 or 2 coats.



Care & Maintenance

Regular cleaning and maintenance will prolong the life of Weberfloor Road Marking. Regular cleaning using a single or double-headed rotary scrubber with alkaline detergent is recommended.

SAINT-GOBAIN (SINGAPORE) PTE LTD

2 Venture Drive, #13-18,
Vision Exchange, Singapore 608526

(65) 63308288 (65) 63308289

eis.info@saint-gobain.com www.saint-gobain.sg

SAINT-GOBAIN WEBER (M) SDN BHD

No 29 & 31, Jalan TIAJ 2/1, Taman Industri Alam Jaya,
42300 Bandar Puncak Alam, Selangor D E, Malaysia

(603) 60389498/97/89 (603) 6038 9507

info.webermalaysia@saint-gobain.com www.mys.weber

Weberfloor Road Marking

Modified acrylic chlorinated rubber road marking

CONSUMPTION

Approx. 0.3 litre per m² @200µ.

STORAGE & PACKING

Weberfloor Road Marking is available in 5 kg and 20 kg sets.
Shelf of 12 months if unopened, and kept in dry and cool conditions.

COLOURS

Black, White, Yellow and Red
Colour may change on exposure to UV.

CLEANING

All tools and equipment should be cleaned immediately with thinner before product hardens.

HEALTH AND SAFETY

Good ventilation is required, if not, a portable exhaust fan shall be used. Wear protective clothing, gloves, and goggles during mixing and application process. Handle with care and in the event of eyes and skin contact, wash with plenty of water, and seek medical attention if irritation persists. Please keep out of reach of children.

*Note: Users must always refer to the most recent TDS which can be downloaded from our website www.saint-gobain.sg. Any amendment to the requirements or information obtained from this TDS excludes the responsibility of Saint Gobain Singapore. Copies of which will be supplied upon request (Version Sept '23).



SAINT-GOBAIN (SINGAPORE) PTE LTD

2 Venture Drive, #13-18,
Vision Exchange, Singapore 608526

(65) 63308288 (65) 63308289

eis.info@saint-gobain.com www.saint-gobain.sg

SAINT-GOBAIN WEBER (M) SDN BHD

No 29 & 31, Jalan TIAJ 2/1, Taman Industri Alam Jaya,
42300 Bandar Puncak Alam, Selangor D E, Malaysia

(603) 60389498/97/89 (603) 6038 9507

info.webermalaysia@saint-gobain.com www.mys.weber